

### Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

#### Listing of Claims:

1. (currently amended) A device for retaining a fuel pump in a fuel container of a motor vehicle, with a pump holder, with first retaining means of the pump holder, provided for supporting on a baffle pot, and with second retaining means of the pump holder, provided for supporting the fuel pump, and with a damping device connecting the first and the second retaining means to one another, the retaining means being manufactured from plastic, the first retaining means, the second retaining means and the damping device being manufactured as a single piece, in that the damping device has arms which are angled away from each other, and in that during a movement of the fuel pump the arms are subject to at least a torsional or a bending load, wherein the arms of the damping device ~~has~~ include at least one first vertical arm extending substantially in a vertical direction and ~~at least one first and second horizontal arm~~ arms extending substantially horizontally and angled away from the first vertical arm, the first and second horizontal arms being spaced apart in the vertical direction, and ~~in that~~ at least one of the first and the second horizontal arms is designed as an annular element.
2. (currently amended) The device as claimed in claim 1, wherein a second vertical arm is ~~arranged between~~ connects the first horizontal arm and ~~[[a]] the second horizontal arm, which~~ and wherein only the second horizontal arm of the arms is directly connected to the second retaining means.
3. (previously presented) The device as claimed in claim 1, wherein the first retaining means are designed such that they are supported radially on the inside of the baffle pot and such that they rest axially.

4. (previously presented) The device as claimed in claim 1, wherein the second retaining means have a pipe length surrounding the fuel pump.
5. (previously presented) The device as claimed in claim 4, wherein the second retaining means have latching hooks, arranged on the pipe length, for retaining the fuel pump.
6. (previously presented) The device as claimed in claim 1, wherein the first vertical arm has a radially inwardly pointing hook, and in that the hook limits the vertical movement of the second retaining means.
7. (previously presented) The device as claimed in claim 4, wherein an annular element connected to the first retaining means has a radially inwardly pointing supporting element situated opposite the pipe length at a designated distance.
8. (previously presented) The device as claimed in claim 1, wherein the single-piece component comprising first and second retaining means and the damping device is manufactured from plastic by injection molding.
9. (previously presented) The device as claimed in claim 1, wherein the fuel pump has an annular, elastomeric sealing element for the annular sealing of an opening arranged in the bottom region of the baffle pot.
10. (previously presented) The device as claimed in claim 9, wherein the sealing element has an obliquely angled sealing lip, and in that the free end of the sealing lip rests on the bottom of the baffle pot.
11. (previously presented) The device as claimed in claim 2, wherein the first retaining means are designed such that they are supported radially on the inside of the baffle pot and such that they rest axially.

12. (previously presented) The device as claimed in claim 2, wherein the second retaining means have a pipe length surrounding the fuel pump.
13. (previously presented) The device as claimed in claim 3, wherein the second retaining means have a pipe length surrounding the fuel pump
14. (previously presented) The device as claimed in claim 2, wherein the first vertical arm has a radially inwardly pointing hook, and in that the hook limits the vertical movement of the second retaining means.
15. (previously presented) The device as claimed in claim 3, wherein the first vertical arm has a radially inwardly pointing hook, and in that the hook limits the vertical movement of the second retaining means.
16. (previously presented) The device as claimed in claim 2, wherein the single-piece component comprising first and second retaining means and the damping device is manufactured from plastic by injection molding.
17. (previously presented) The device as claimed in claim 2, wherein the fuel pump has an annular, elastomeric sealing element for the annular sealing of an opening arranged in the bottom region of the baffle pot.
18. (previously presented) The device as claimed in claim 3, wherein the single-piece component comprising first and second retaining means and the damping device is manufactured from plastic by injection molding.
19. (previously presented) The device as claimed in claim 3, wherein the fuel pump has an annular, elastomeric sealing element for the annular sealing of an opening arranged in the bottom region of the baffle pot.

20. (new) The device as claimed in claim 2, wherein only the first horizontal arm of the first and second horizontal arms is connected directly to the at least one first vertical arm, and wherein only the at least one vertical arm of the arms is directly connected to the first retaining means.